

Datasheet

compact PC keyboard for the industrial sector

AK-4100



Article ID	AK-4100
Model	IndustrialKey™
Surface	plastic keys
Execution	desktop housing, office keyboards
Layout	compact layout
Number of keys	83
Key switch technology	mechanical scissor balancing
Switching power	0,58 N
Switch travel	2,5 mm
Switching cycle	ca. 10 Mio.
Pointing device	without
Front	plastic
Enclosure material	plastic
IP protection level	IP20
Operating temperature	0°C ... +50°C
Storage temperature	-20°C ... +60°C
weight	500 g

Datasheet

compact PC keyboard for the industrial sector

AK-4100



Dimensions	282 x 132 x 25 mm
Interface	USB 1.1, PS2
Country version	DE, US andere Länderlayouts auf Anfrage
Colour	weiß, schwarz
Special function	without
Certification	CE, FCC, RoHS
Article number	USB: AK-4100-U-W (weiß), AK-4100-U-B (schwarz) PS2: AK-4100-P-W (weiß), AK-4100-P-B (schwarz)
Application	Industry, , Apparatus engineering,
alternative according Cherry productnumber	G84-4100LCADE-0, G84-4100LCADE-2, G84-4100LCAES-0, G84-4100LCAFR-0, G84-4100LCAFR-2, G84-4100LCAGB-0, G84-4100LCAGB-2, G84-4100LCAUS-0, G84-4100LCAUS-2, G84-4100LCMBE-0, G84-4100LCMBE-2, G84-4100LCMCD-2, G84-4100LCMCH-0, G84-4100LCMCH-2, G84-4100LCMDE-0, G84-4100LCMDE-2, G84-4100LCMES-0, G84-4100LCMES-2, G84-4100LCMEU-0, G84-4100LCMEU-2, G84-4100LCMFR-0, G84-4100LCMFR-2, G84-4100LCMGB-0, G84-4100LCMGB-2, G84-4100LCMIT-0, G84-4100LCMIT-2, G84-4100LCMPN-0, G84-4100LCMPN-2, G84-4100LCMPO-0, G84-4100LCMPO-2, G84-4100LCMRB-0, G84-4100LCMRB-2, G84-4100LCMUS-0, G84-4100LCMUS-2, G84-4100LPADE-0, G84-4100LPAEU-0, G84-4100LPAGB-0, G84-4100LPAUS-0, G84-4100LPAUS-2, G84-4100LPMDE-0, G84-4100LPMDE-2, G84-4100LPMEU-0, G84-4100LPMEU-2, G84-4100LPMUS-0