

## Datasheet

### High-performance-Pyrometer Optris CSlaser LT

OPTCSLLT



<b>Article ID</b>	OPTCSLLT
<b>Model</b>	Hochleistungs-Pyrometer Optris CSlaser LT
<b>Variante</b>	integrated electronic
<b>Temperature range</b>	-30°C ... 1000°C
<b>Spectral range</b>	8 ... 14 $\mu\text{m}$
<b>Optical resolution (D:S)</b>	50 : 1
<b>Spot size: up from</b>	1,4 mm
<b>System accuracy</b>	$\pm 1^\circ\text{C}$ or $\pm 1\%$ at ambient temperature $23\pm 5^\circ\text{C}$
<b>Repeatability</b>	$\pm(0,5\%$ of reading $+0,5^\circ\text{C}$ ) at ambient temperature $23\pm 5^\circ\text{C}$
<b>Emissivity</b>	0,10 ... 1,10
<b>Response time</b>	150 ms
<b>Temperature resolution</b>	0,1 K
<b>Power supply</b>	5 - 30 VDC
<b>Outputs</b>	4 ... 20 mA, Alarm output 0-30V / 500 mA (open collector)
<b>Interface optional</b>	USB
<b>Software</b>	optris CompactConnect (Windows), IRmobile (Android)

## Datasheet

### High-performance-Pyrometer Optris CSlaser LT OPTCSLLT



<b>Ambient temperature sensor head</b>	-20°C ... 85°C
<b>Ambient temperature electronics</b>	-20°C ... 85°C
<b>Sighting scope</b>	Double laser
<b>Application</b>	Non-metals
<b>Manual</b>	<a href="#">Bedienungsanleitung Optris CSlaser Serie</a>