

## Datasheet

### Miniature-Infrared-Thermometer Optris CSmicro LT15

OPTCSMALT15



<b>Article ID</b>	OPTCSMALT15
<b>Model</b>	Miniature-Infrared-Thermometer Optris CSmicro LT15
<b>Variante</b>	integrated electronic
<b>Temperature range</b>	-50°C ... 1030°C
<b>Spectral range</b>	8 ... 14 $\mu\text{m}$
<b>Optical resolution (D:S)</b>	15 : 1
<b>Spot size: up from</b>	0,8 mm
<b>System accuracy</b>	$\pm 1^\circ\text{C}$ or $\pm 1\%$ at ambient temperature $23\pm 5^\circ\text{C}$
<b>Repeatability</b>	$\pm(0,5\%$ of reading $+0,5^\circ\text{C})$ at ambient temperature $23\pm 5^\circ\text{C}$
<b>Emissivity</b>	0,100 - 1,100
<b>Response time</b>	14 ms
<b>Temperature resolution</b>	0,1 K
<b>Power supply</b>	5 - 30 VDC
<b>Outputs</b>	4 ... 20 mA, Alarm output 0-30V / 500 mA (open collector)
<b>Thermal Sensitivity (NETD)</b>	50 mK
<b>Interface optional</b>	USB

## Datasheet

### Miniature-Infrared-Thermometer Optris CSmicro LT15 OPTCSMALT15



<b>Software</b>	optris CompactConnect (Windows), IRmobile (Android)
<b>Ambient temperature sensor head</b>	-20°C ... 120°C
<b>Ambient temperature electronics</b>	-20°C ... 75°C
<b>Sighting scope</b>	LED aiming
<b>Application</b>	Non-metals
<b>Manual</b>	<a href="#">Manual Optris CSmicro series</a>