

## Datasheet

### Calibration reference pyrometer Optris CTlaser DCI OPTCTLLTSFDCI



<b>Article ID</b>	OPTCTLLTSFDCI
<b>Model</b>	Kalibrier-Referenz-IR-Thermometer Optris CTlaser LT DCI
<b>Variante</b>	separate electronics box with programming buttons and display
<b>Temperature range</b>	-50°C ... 975°C
<b>Spectral range</b>	8 ... 14 µm
<b>Optical resolution (D:S)</b>	75 : 1
<b>Spot size: up from</b>	16mm @ 1200 mm
<b>Emissivity</b>	0,10 ... 1,10
<b>Response time</b>	120 ms
<b>Power supply</b>	8 - 36 VDC
<b>Outputs</b>	0/4 ... 20 mA, 0 ... 5/10 V, Thermocouple J+K, Alarm output 24V / 50 mA (open collector), Relay: 2 x 60 VDC / 0,4 A optically isolated (optional)
<b>Thermal Sensitivity (NETD)</b>	100 mK
<b>Interface optional</b>	USB, RS232, RS485, Profibus DP, Ethernet, CAN
<b>Software</b>	optris CompactConnect (Windows), IRmobile (Android)
<b>Ambient temperature sensor head</b>	0°C ... 50°C

## Datasheet

### Calibration reference pyrometer Optris CTlaser DCI OPTCTLLTSFDCI



<b>Ambient temperature electronics</b>	0°C ... 50°C
<b>Sighting scope</b>	Double laser
<b>Application</b>	calibration refrence
<b>Manual</b>	<a href="#">Bedienungsanleitung Optris CTlaser Serie</a>