

Datasheet

Compact-Infrared-Thermometer Optris CT LT22

OPTCTLT20



Article ID	OPTCTLT20
Model	Compact-Infrared-Thermometer Optris CT LT20
articlenumber	OPTCTLT20, OPTCTLT20CF, OPTCTLT20CB3, OPTCTLT20CFCB3, OPTCTLT20CB8, OPTCTLT20CFCB8, OPTCTLT20CB15, OPTCTLT20CFCB15
Variante	separate electronics box with programming buttons and display
Temperature range	-50°C ... 975°C
Spectral range	8 ... 14 µm
Optical resolution (D:S)	22 : 1
Spot size: up from	0,6 mm
System accuracy	±1°C or ±1% at ambient temperature 23±5°C
Repeatability	±(0,5% of reading +0,5°C) at ambient temperature 23±5°C
Emissivity	0,10 ... 1,10
Response time	150 ms
Temperature resolution	0,1 K
Power supply	8 - 36 VDC
Outputs	0/4 ... 20 mA, 0 ... 5/10 V, Thermocouple J+K, Alarm output 24V / 50 mA (open collector), Relay: 2 x 60 VDC / 0,4 A optically isolated (optional)

Datasheet

Compact-Infrared-Thermometer Optris CT LT22

OPTCTLT20



Thermal Sensitivity (NETD)	50 mK
Interface optional	USB, RS232, RS485, Profibus DP, Ethernet, CAN
Software	optris CompactConnect (Windows), IRmobile (Android)
Ambient temperature sensor head	-20°C ... 180°C
Ambient temperature electronics	-20°C ... 85°C
Sighting scope	without
Application	Non-metals
Manual	Manual Optris CT series
Alternative product numbers	CT-SF22-C1, CT-SF22-C15, CT-SF22-C3, CT-SF22-C8, CT-CF22-C1, CT-CF22-C15, CT-CF22-C3, CT-CF22-C8