

Datenblatt

N-TRON PoE+ 2-Port Midspan-Injektor

1000-POE+



| | |
|----------------------------|---|
| Bezeichnung | 1000-POE+ |
| Modell | N-TRON Midspan-Injektor |
| Schutzgrad | IP30 |
| Typ | Unmanaged Switch |
| Gesamtzahl Ports | 2 |
| 10/100/1000 Kupfer | 1 |
| Übertragungsrate | 10/100/1000 MBit/s |
| Betriebstemperatur | -40°C ... +80°C |
| Lagertemperatur | -40°C ... +85°C |
| Versorgungsspannung | 10-30 VDC |
| Gehäusematerial | Metall |
| Montage | DIN-Hutschiene |
| Abmessungen | 25,4 x 109,2 x 92,2 mm |
| Gewicht | 270 g |
| Besonderheiten | MTBF: 2 Mio. Stunden Schock: 200G/10ms Vibration: 50G/Triaxial 5-200Hz ESD: +/- 16kV |

Datenblatt

N-TRON PoE+ 2-Port Midspan-Injektor

1000-POE+



Zertifizierung

ABS Type Approval for Shipboard Applications, ANSI/ISA 12.12.01-2015 Class I and II, Div. 2 and Class III, Div. 1 and 2, Groups A, B, C and D Hazardous Locations, T4 UL508 Industrial Control Equipment
ANSI/ISA-12.12.01-2013, Class I and II, Division 2 and Class III, Divisions 1, CAN/CSA-C22.2 No. 213-15, Hazardous Locations, CAN/CSA-C22.2 No. 14-13, Industrial Control Equipment, Canada C22.2 No. 14; C22.2 No. 213-M1987 Class I, Division 2 Hazardous Locations, Designed to Comply with: IEEE 1613 (Electric Utility Substations), NEMA TS1/TS2 (Traffic Control), Emissions: FCC Title 47, Part 15, Radio Frequency Devices, Subpart B, ANSI C63.4-2009; Industry Canada ICES-003, EN 55032, EN 61000-3-2, EN61000-3-3, EMC Directive 2014/30/EU, EN 55024, EN 61000-6-2, EN 61000-4-2 (ESD); EN 61000-4-3 (RFAM); EN 61000-4-4 (EFT); EN 61000-4-5 (SURGE); EN 61000-4-6 (RFCM); EN 61000-4-8 (PFMF); EN 61000-4-11 (VDI), LV Directive 2014/35/EU GOST-R, Product Safety: USA UL508 Industrial Control Equipment, Rail: EN 50155, EN50121, EN61373, RoHS

Anzahl PoE+ Ports (IEEE 802.3at)

1