

Datenblatt

N-TRON Unmanaged 8-Port Ethernet Switch

108TX



Bezeichnung	108TX
Modell	N-TRON Unmanaged Ethernet Switch
Typ	Unmanaged Switch
Gesamtanzahl Ports	8
10/100 Kupfer	8
Gehäusematerial	Metall
Betriebstemperatur	-40°C ... +70°C
Lagertemperatur	-40°C ... +85°C
Gewicht	400 g
Abmessungen	38 x 89 x 90 mm
Besonderheiten	MTBF: 2 Mio. Stunden Schock: 100G/10ms Vibration: 50G/Triaxial 5-200Hz ESD: +/- 16kV
Versorgungsspannung	10-30 VDC
Übertragungsrate	10/100 Mbit/s
Anzahl MAC Adressen	2048
Montage	DIN-Hutschiene

Datenblatt

N-TRON Unmanaged 8-Port Ethernet Switch

108TX



Schutzgrad

IP30

Zertifizierung

Product Safety: USA UL508 Industrial Control Equipment, ANSI/ISA 12.12.01-2015 Class I and II, Div. 2 and Class III, Div. 1 and 2, Groups A, B, C and D Hazardous Locations, T4

UL508 Industrial Control Equipment

ANSI/ISA-12.12.01-2013, Class I and II, Division 2 and Class III, Divisions 1, Canada C22.2 No. 14; C22.2 No. 213-M1987 Class I, Division 2 Hazardous Locations, CAN/CSA-C22.2 No. 213-15, Hazardous Locations, CAN/CSA-C22.2 No. 14-13, Industrial Control Equipment, Emissions: FCC Title 47, Part 15, Radio Frequency Devices, Subpart B, ANSI C63.4-2009; Industry Canada ICES-003, EN 55032, EN 61000-3-2, EN61000-3-3, EN 55024, EN 61000-6-2, EN 61000-4-2 (ESD); EN 61000-4-3 (RFAM); EN 61000-4-4 (EFT); EN 61000-4-5 (SURGE); EN 61000-4-6 (RFCM); EN 61000-4-8 (PFMF); EN 61000-4-11 (VDI), Rail: EN 50155, EN50121, EN61373, ABS Type Approval for Shipboard Applications, Designed to Comply with: IEEE 1613 (Electric Utility Substations), NEMA TS1/TS2 (Traffic Control), EMC Directive 2014/30/EU, LV Directive 2014/35/EU GOST-R, RoHS