

Datenblatt

N-TRON Managed 8-Port Gigabit Switch

NT24k-8TX



Bezeichnung	NT24k-8TX
Modell	N-TRON Managed Gigabit Switch
Schutzgrad	IP30
Typ	Managed Switch
Gesamtzahl Ports	8
10/100/1000 Kupfer	8
Übertragungsrate	10/100/1000 MBit/s
Anzahl MAC Adressen	8192
Betriebstemperatur	-40°C ... +85°C
Lagertemperatur	-40°C ... +85°C
Versorgungsspannung	10-49 VDC
Gehäusematerial	Metall
Montage	DIN-Hutschiene
Abmessungen	56,4 x 149,3 x 140,7 mm
Gewicht	760 g

Datenblatt

N-TRON Managed 8-Port Gigabit Switch

NT24k-8TX



Besonderheiten

Real-Time Ring, Priority Queuing, Monitoring, IGMP, RMON und SNMP
MTBF: 2 Mio. Stunden
Schock: 100G/10ms
Vibration: 50G/Triaxial 5-200Hz
ESD: +/- 16kV

Zertifizierung

ABS Type Approval for Shipboard Applications, ANSI/ISA 12.12.01-2015 Class I and II, Div. 2 and Class III, Div. 1 and 2, Groups A, B, C and D Hazardous Locations, T4 UL508 Industrial Control Equipment
ANSI/ISA-12.12.01-2013, Class I and II, Division 2 and Class III, Divisions 1, CAN/CSA-C22.2 No. 213-15, Hazardous Locations, CAN/CSA-C22.2 No. 14-13, Industrial Control Equipment, Canada C22.2 No. 14; C22.2 No. 213-M1987 Class I, Division 2 Hazardous Locations, Designed to Comply with: IEEE 1613 (Electric Utility Substations), NEMA TS1/TS2 (Traffic Control), Emissions: FCC Title 47, Part 15, Radio Frequency Devices, Subpart B, ANSI C63.4-2009; Industry Canada ICES-003, EN 55032, EN 61000-3-2, EN61000-3-3, EMC Directive 2014/30/EU, EN 55024, EN 61000-6-2, EN 61000-4-2 (ESD); EN 61000-4-3 (RFAM); EN 61000-4-4 (EFT); EN 61000-4-5 (SURGE); EN 61000-4-6 (RFCM); EN 61000-4-8 (PFMF); EN 61000-4-11 (VDI), LV Directive 2014/35/EU GOST-R, Product Safety: USA UL508 Industrial Control Equipment, Rail: EN 50155, EN50121, EN61373, RoHS