

## Datenblatt

### Sixnet Unmanaged 6-Port Ethernet Switch

SL-6ES-4/5



<b>Bezeichnung</b>	SL-6ES-4/5
<b>Modell</b>	Sixnet Unmanaged Ethernet Switch
<b>Typ</b>	Unmanaged Switch
<b>Gesamtanzahl Ports</b>	6
<b>10/100 Kupfer</b>	4
<b>100 Glasfaser</b>	2
<b>Gehäusematerial</b>	UL94V0 Lexan
<b>Betriebstemperatur</b>	-40°C ... +60°C
<b>Lagertemperatur</b>	-40°C ... +85°C
<b>Gewicht</b>	170 g
<b>Abmessungen</b>	38 x 107 x 95 mm
<b>Besonderheiten</b>	MTBF: 1 Mio. Stunden Schock: 100G/10ms Vibration: 50G/Triaxial 5-200Hz ESD: +/- 16kV
<b>Versorgungsspannung</b>	10-30 VDC
<b>Übertragungsrate</b>	10/100 Mbit/s
<b>Anzahl MAC Adressen</b>	1024

## Datenblatt

### Sixnet Unmanaged 6-Port Ethernet Switch

SL-6ES-4/5



#### Montage

DIN-Hutschiene, Wandmontage

#### Schutzgrad

IP30

#### Zertifizierung

Product Safety: USA UL508 Industrial Control Equipment, ANSI/ISA 12.12.01-2015 Class I and II, Div. 2 and Class III, Div. 1 and 2, Groups A, B, C and D Hazardous Locations, T4

UL508 Industrial Control Equipment

ANSI/ISA-12.12.01-2013, Class I and II, Division 2 and Class III, Divisions 1, CAN/CSA-C22.2 No. 213-15, Hazardous Locations, CAN/CSA-C22.2 No. 14-13, Industrial Control Equipment, Emissions: FCC Title 47, Part 15, Radio Frequency Devices, Subpart B, ANSI C63.4-2009; Industry Canada ICES-003, EN 55032, EN 61000-3-2, EN61000-3-3, ABS Type Approval for Shipboard Applications, RoHS