

Datenblatt

Sixnet Unmanaged 8-Port Ethernet Switch

SL-8ES-1



Bezeichnung	SL-8ES-1
Modell	Sixnet Unmanaged Ethernet Switch
Schutzgrad	IP30
Typ	Unmanaged Switch
Gesamtzahl Ports	8
10/100 Kupfer	8
Übertragungsrate	10/100 MBit/s
Anzahl MAC Adressen	1024
Betriebstemperatur	-40°C ... +60°C
Lagertemperatur	-40°C ... +85°C
Versorgungsspannung	10-30 VDC
Gehäusematerial	UL94V0 Lexan
Montage	DIN-Hutschiene, optional Wandmontage
Abmessungen	38,1 x 106,7 x 82,8 mm
Gewicht	170 g

Datenblatt

Sixnet Unmanaged 8-Port Ethernet Switch

SL-8ES-1



Besonderheiten

MTBF: 1 Mio. Stunden
Schock: 100G/10ms
Vibration: 50G/Triaixial 5-200Hz
ESD: +/- 16kV

Zertifizierung

ABS Type Approval for Shipboard Applications, ANSI/ISA 12.12.01-2015 Class I and II, Div. 2 and Class III, Div. 1 and 2, Groups A, B, C and D Hazardous Locations, T4 UL508 Industrial Control Equipment
ANSI/ISA-12.12.01-2013, Class I and II, Division 2 and Class III, Divisions 1, CAN/CSA-C22.2 No. 213-15, Hazardous Locations, CAN/CSA-C22.2 No. 14-13, Industrial Control Equipment, Emissions: FCC Title 47, Part 15, Radio Frequency Devices, Subpart B, ANSI C63.4-2009; Industry Canada ICES-003, EN 55032, EN 61000-3-2, EN61000-3-3, Product Safety: USA UL508 Industrial Control Equipment