

## Datenblatt

### Sixnet Managed 16-Port Ethernet Switch

SLX-16MS-1



Bezeichnung	SLX-16MS-1
Modell	Sixnet Managed 16-Port Switch
Typ	Managed Switch
Gesamtanzahl Ports	16
10/100 Kupfer	16
Gehäusematerial	Aluminium
Betriebstemperatur	-40°C ... +75°C
Lagertemperatur	-40°C ... +85°C
Gewicht	340 g
Abmessungen	54 x 152,9 x 121,9 mm
Besonderheiten	Real-Time Ring, Priority Queuing, IGMP, RMON und SNMP MTBF: 2 Mio. Stunden Schock: 100G/10ms Vibration: 50G/Triaxial 5-200Hz ESD: +/- 16kV
Versorgungsspannung	10-30 VDC
Übertragungsrate	10/100 Mbit/s
Anzahl MAC Adressen	2048
Montage	DIN-Hutschiene

## Datenblatt

### Sixnet Managed 16-Port Ethernet Switch

SLX-16MS-1



#### Schutzgrad

IP30

#### Zertifizierung

Product Safety: USA UL508 Industrial Control Equipment, ANSI/ISA 12.12.01-2015 Class I and II, Div. 2 and Class III, Div. 1 and 2, Groups A, B, C and D Hazardous Locations, T4

UL508 Industrial Control Equipment

ANSI/ISA-12.12.01-2013, Class I and II, Division 2 and Class III, Divisions 1, CAN/CSA-C22.2 No. 213-15, Hazardous Locations, CAN/CSA-C22.2 No. 14-13, Industrial Control Equipment, Emissions: FCC Title 47, Part 15, Radio Frequency Devices, Subpart B, ANSI C63.4-2009; Industry Canada ICES-003, EN 55032, EN 61000-3-2, EN61000-3-3, ABS Type Approval for Shipboard Applications