

Datenblatt

Sixnet Managed 8-Port Gigabit Switch

SLX-8MG-1



Bezeichnung	SLX-8MG-1
Modell	Sixnet Managed Gigabit Switch
Typ	Managed Switch
Gesamtanzahl Ports	8
10/100/1000 Kupfer	8
Gehäusematerial	Aluminium
Betriebstemperatur	-40°C ... +75°C
Lagertemperatur	-40°C ... +85°C
Gewicht	280 g
Abmessungen	69,8 x 132,1 x 109,2 mm
Besonderheiten	Real-Time Ring, Priority Queuing, IGMP, RMON und SNMP MTBF: 2 Mio. Stunden Schock: 100G/10ms Vibration: 50G/Triaxial 5-200Hz ESD: +/- 16kV
Versorgungsspannung	10-30 VDC
Übertragungsrate	10/100/1000 Mbit/s
Anzahl MAC Adressen	8192
Montage	DIN-Hutschiene, Wandmontage

Datenblatt

Sixnet Managed 8-Port Gigabit Switch

SLX-8MG-1



Schutzgrad

IP30

Zertifizierung

Product Safety: USA UL508 Industrial Control Equipment, ANSI/ISA 12.12.01-2015 Class I and II, Div. 2 and Class III, Div. 1 and 2, Groups A, B, C and D Hazardous Locations, T4

UL508 Industrial Control Equipment

ANSI/ISA-12.12.01-2013, Class I and II, Division 2 and Class III, Divisions 1,

Emissions: FCC Title 47, Part 15, Radio Frequency Devices, Subpart B, ANSI C63.4-2009; Industry Canada ICES-003, EN 55032, EN 61000-3-2, EN61000-3-3, ABS Type Approval for Shipboard Applications, Designed to Comply with: IEEE 1613 (Electric Utility Substations), NEMA TS1/TS2 (Traffic Control)