

## Datenblatt

### Sixnet Managed 8-Port Ethernet Switch

SLX-8MS-1



<b>Bezeichnung</b>	SLX-8MS-1
<b>Modell</b>	Sixnet Managed Ethernet Switch
<b>Typ</b>	Managed Switch
<b>Gesamtanzahl Ports</b>	8
<b>10/100 Kupfer</b>	8
<b>Gehäusematerial</b>	Aluminium
<b>Betriebstemperatur</b>	-40°C ... +75°C
<b>Lagertemperatur</b>	-40°C ... +85°C
<b>Gewicht</b>	280 g
<b>Abmessungen</b>	40,7 x 132,1 x 110,2 mm
<b>Besonderheiten</b>	Real-Time Ring, Priority Queuing, IGMP, RMON und SNMP MTBF: 2 Mio. Stunden Schock: 100G/10ms Vibration: 50G/Triaxial 5-200Hz ESD: +/- 16kV
<b>Versorgungsspannung</b>	10-30 VDC
<b>Übertragungsrate</b>	10/100 Mbit/s
<b>Anzahl MAC Adressen</b>	2048
<b>Montage</b>	DIN-Hutschiene

## Datenblatt

### Sixnet Managed 8-Port Ethernet Switch

SLX-8MS-1



#### Schutzgrad

IP30

#### Zertifizierung

Product Safety: USA UL508 Industrial Control Equipment, ANSI/ISA 12.12.01-2015 Class I and II, Div. 2 and Class III, Div. 1 and 2, Groups A, B, C and D Hazardous Locations, T4

UL508 Industrial Control Equipment

ANSI/ISA-12.12.01-2013, Class I and II, Division 2 and Class III, Divisions 1,

Canada C22.2 No. 14; C22.2 No. 213-M1987 Class I, Division 2 Hazardous

Locations, Emissions: FCC Title 47, Part 15, Radio Frequency Devices, Subpart B,

ANSI C63.4-2009; Industry Canada ICES-003, EN 55032, EN 61000-3-2,

EN61000-3-3, ABS Type Approval for Shipboard Applications